

# RURY I KOLANA SPALINOWE

## Cennik



Cena netto/cena brutto [zł]

		Średnica	120	130	150	160	180	200	
Rura 250			40,7/50	42/52	43/53	44/54	44/57	50/62	
Rura 500			54/66	56/69	56/69	58/72	60/72	63/78	
Rura 1000			70/87	73/89	77/95	80/99	86/106	90/110	
Rura 500 żebrowana					88/108		94/116	97/119	
Kolano 90°			70/87	75/92	76/93	78/96	79/97	84/103	
Redukcja	120			41/50	60/74	60/74			
	130				43/53	60/74	60/76		
	150					44/54	46/57	46/57	
	160						44/57	60/74	
	180							60/74	
Rozeta			17,6/22	19/23	20/24	21/26	21/26	22/28	
Wkładka dwuścienna			39/47	40/49	42/49	44/54	46/57	48/59	
Wkładka jednościenna			24/30	25/31	26/32	28/34	29/36	32/39	
Szyber 250			64/79	66/81	70/87	70/87	73/90	79/97	
Przejście ceramiczne	150		88/108						
	160								
	180								
	200								
Trójnik 90°			114/140	120/148	125/154	133/164	139/171	152/187	
Trójnik 45°			130/160	120/148	125/154		139/171		
Złączka męska			31/38	32/39	33/41	35/43	36/45	41/50	
Złączka żeńska			31/38	32/39	33/41	35/43	36/45	41/50	

1. Zastosowanie: Budowa przyłączy kominowych, do kominków, pieców i kotłów na paliwo stałe
2. Elementy systemu nie mogą stanowić samodzielnego komina
3. Max temperatura pracy: 1000°C Grubość blachy: 2,0 mm